GF3 *Glass Fiber Ø 3 mm - incl. digital meter counter*

Cable pulling system for pipe inner diameter 9 – 45 mm
Item no.: **10192** | **10193** | **10195**

VIDEO
GF3
Click here Video



KNICKSCHUTZ
KINK PROTECTION

KG 130

PATENTED

Automatic glide back protection
(only stops the RG7 Guiding head incl. kink protection)

Integrated digital meter counter – m/ft



Front end: Guiding head with RTG Ø 6 mm front thread, swivel and kink protection

Rear end: Kink protection with RTG Ø 6 mm inner thread

Attention! electric conductive

Click here Productinformation

Accessory box (16-parts)




Easy service opening / accessory box



Just open one screw



Accessory box 16-parts

Rod	Rec. pipe ID	Bending radius w. e. joint	Bending radius rod	Breaking load	Total breaking load
Ø					
3 mm	9 – 45 mm	38 mm	28 mm	450 kg	130 kg

DATA

ITEM NO.	**10192**	**10193**	**10195**
LENGTH	20 m	30 m	50 m
TOTAL WEIGHT	1,28 kg	1,38 kg	1,58 kg
MATERIAL ROD	Fiberglass core with PP sheath		
BENDING RADIUS	38 mm		
PIPE INNER Ø	optimal from 9 mm - 45 mm		
DIMENSION	L: 295 mm x W: 245 mm x H: 74 mm		
EAN-CODE	9120045476729	9120045477122	9120045477139

DESCRIPTION

GF3 - Cable pulling tool incl. digital meter counter, glass fibre rod Ø 3 mm with kink protection ending joint and patented guiding head with swivel. Stowed in a shock-proof plastic box. The GF3 plastic box can be opened with only a single screw for service work. The glide-back protection (only stops the RG7 guiding head, including kink protection) prevents the fibreglass rod from accidentally slipping back into the box. The scope of delivery includes an 16-piece accessory set. The newly developed kink protection technology makes it possible to overcome bending radii of up to R = 38 mm. Total breaking load of 130 kg refers to the glass fibre rod incl. kink protection joints.
Optimal field of application: for pipe inner dimension 9 mm - 45 mm.

Scope of supply: 1 x GF3 incl. metre counter in plastic box, kink protection ending joint on both sides (front end/rear end), contents of the accessory box: 1 x RG7 guiding head with swivel, 1 x kink protection ending joint RTG Ø 6 mm, 1 x pulling grip, 1 x special glue 3 g, 1 x cable pull loop (Ø 14 mm outside), 6 x adhesive join-set Ø 3 mm, 3 x pulling eyelet-set Ø 7 mm, 1 x starting head Ø 11 mm, 1 x connecting joint, 2 x mounting-wrench, 1 x button battery CR2032

ADVANTAGES

- Integrated digital meter counter
- Guiding head with swivel and kink protection
- Autom. glide back protection (only stops the RG7 guiding head, including kink protection)
- Easy service access
- Extremly shoockproof box
- Also for occupied pipes
- Inspection camera RC2/RC3 compatible
- Total breaking load 130 kg

INFORMATION

Compatible with:

RC2 Inspection camera
30 m - Item no.: 10140
50 m - Item no.: 10141



Click here Productinformation

RC3 Inspection camera (digital)
15 m - Item no. 10214



Click here Productinformation