POLYESTER CABLE PULLING ROPE *incl. steel reel*


Rope Ø 10 mm for CW 800 E capstan winch
Item no.: **10167** | **10168**

VIDEO
CW 800 E Capstan winch
Click here Video

KG 1640



Click here Productinformation



Detail images







DATA		
ITEM NO.	**10167**	**10168**
ROPE Ø	Ø 10 mm	Ø 10 mm
ROPE LENGTH	120 m	200 m
REEL BASKET Ø	514 mm	770 mm
INTERNAL REEL BASKET	70 mm	98 mm
DIMENSION	L 550 x B 210 x H 660 mm	L 830 x B 410 x H 900 mm
TOTAL WEIGHT	15 kg	30 kg
EAN-CODE	9120045475906	9120045475913
TOTAL BREAKING LOAD	1640 kg	
MATERIAL ROPE	Polyester - Rope	
LOOP	2x spliced-in loops	

ADVANTAGES

- Spliced loops at the start and end of the rope
- Low rope elongation
- Practical reel for controlled winding and unwinding of the rope
- Reel Ø 514 mm with extendable feet
- Reel Ø 770 mm mobile with wheel
- Reel with parking brake

DESCRIPTION

RUNPOTEC polyester pulling ropes are optimally suited for horizontal cable pulling with the RUNPOTEC CW 800 E capstan winch. RUNPOTEC recommends using the connecting swirl with swivel for horizontal cable pulling. It reduces frictional resistance and protects the cable and the feed system. The reel allows controlled winding and unwinding of the rope. In addition, the rope is perfectly stowed away and ready for use at any time.The 770 mm reel cage size can be easily rolled and transported due to the integrated wheels. The reel is CDP/powder coated.

Safety instructions: Not suitable for vertical cable pulling, must not be used to carry or lift loads or persons.

Optimal application: for horizontal cable pulling in combination with the CW 800 E capstan winch.

Scope of delivery: 1 x Polyester cable pulling rope Ø 10 mm incl. steel reel


INFORMATION

Accesories:
Connection swirl
incl. swivel
Item no. 10176



Click here Productinformation

Related Pullingsystem:
CW 800 E Capstan winch + Trolley
Item no. 10138



Click here Productinformation