# CAMERA PROBE Ø 9 mm flexible - 0,80 m

for RC2 Inspection camera
Item no.: **20481**

VIDEO
RC2
Click here Video



Click here Productinformation

## DATA

| | |
|---|---|
| ITEM NO. | **20481** |
| WEIGHT KG | 0,169 kg |
| DIMENSION | H 10 mm x DM 200 mm |
| CAMERA HEAD | 300.000 Pixel (720x 576) |
| LIGHTNING | 4 x LED (dimmable) |
| PROTECTION CLASS | IP 67 |
| ANGLE OF VIEW | 64 ° |
| DIAMETER | 9 mm |
| EAN-CODE | 9120045475180 |

## ADVANTAGES

- Flexible gooseneck for individual viewing angle adjustment
- Protection class IP67
- Suitable for RC2 inspection camera
- Angle of view 64°

## DESCRIPTION

Camera head (Ø 9 mm) with flexible gooseneck for the RC2 inspection camera. Ideal for adjusting the viewing angle to suit hard-to-reach areas. Length: 0.80 m.
Features a resolution of 300,000 pixels (720 x 576), IP67 protection rating, a 64° field of view, 4 integrated LEDs and 6-level adjustable LED lighting. Integrated autofocus.
Ideal application: Ideal for short distances with a flexible gooseneck. For inspections of cavity walls, plant, machinery, engines, ventilation systems, control or inspection systems. Ideal for complex cavities, tight corners, shafts, ducts, small passages and many other applications in hard-to-reach areas.

**Scope of supply:** 1 x Endoscope camera probe Ø 9 mm flexible - length: 0,80 m

## INFORMATION

Compatible with:
**RC2 Inspection camera**
50 m - Item no.: 10141



Click here Productinformation