SHAKLE *RTG Ø 6 mm*

for fiberglass rods GF4.5 - GF6 and RUNPOSTICKS
Item no.: **20280**

VIDEO
GF4.5/ GF6
Click here Video



Click here Produktinformation

Application examples:







DATA

ITEM NO.	**20280**
WEIGHT	0,025 kg
DIMENSION	L 44 mm x B 22 mm x H 12 mm
THREAD	RTG Ø 6 mm
MATERIAL	Stainless steel/ Galvanized steel
EAN-CODE	9120045474800

ADVANTAGES

- For attaching cables, pull wires or pull ropes
- RUNPOTEC RTG Ø 6 mm thread
- Stainless steel / Galvanized steel

DESCRIPTION

The robust shackle is ideal for attaching cables, pull-in wires or pull ropes and provides a reliable connection for various applications. It is compatible with GF4 and GF6 fiber optic rods or with RUNPOSTICKS. Thanks to its high-quality stainless steel and galvanized steel construction, it impresses with its durability and high load capacity.
Application video: a short, very informative application video can be viewed by scanning the QR code or on www.RUNPOTEC.com.

Scope of supply: 1 x Shackle with RTG Ø 6 mm thread

INFORMATION

Combinable Pulling systems:

Fiberglass rods
GF4.5 and GF6
Length 30 - 80 m



Click here Produktinformation

RUNPOSTICKS
Comfort - Item no. 10020
Standard - Item no. 10016



Click here Produktinformation