
Anfangsbirne *Ø 20 mm*

für RUNPOTEC Produkte mit THREAD RTG Ø 12 mm inkl. VerbindungsTHREAD
Item no.: **20409**

VIDEO
GF7.5-GF11
Click here Video



Cross section



RTG Ø 12 mm

RTG Ø 6 mm

incl. connection thread
(for flexible leading head or small-sized cable pulling grip)
incl. blind cap
(for thread proctection)

Click here Productinformation

Application images



Can be adapted to roller, shackle and starting head Ø 20 mm, Ø 30 mm



DATA	
ITEM NO.	**20409**
WEIGHT	0,062 kg
DIMENSION	L 47 mm x B 29 mm x DM 20 mm
THREAD	RTG Ø 12 mm
MATERIAL	Stainless steel
EAN-CODE	9120045474411

ADVANTAGES

- Thread RTG Ø 12 mm
- For guide probe or smaller cable pulling grips
- Incl. connecting thread
- Stainless steel
- Leanest head

DESCRIPTION

Starting head Ø 20 mm made of stainless steel for fiberglass rod Ø 7.5 mm, 9 mm, 11 mm, 15 mm - RTG Ø 12 mm thread. The starting head has an additional transition thread to RTG Ø 6 mm to adapt various guide rods (RUNPOSTICKS), guide probes, cable pulling grip (sock) etc.

Scope of supply: 1 x Starting head Ø 20 mm with thread RTG Ø 12 mm, 1x connection thread RTG Ø 6 mm

INFORMATION

Compatible with:
Glasfaserstäbe:
GF7.5, GF9,
GF11, GF15



Click here Productinformation