
Anfangsbirne *Ø 30 mm*

für RUNPOTEC Produkte mit THREAD RTG Ø 12 mm inkl. VerbindungsTHREAD
Item no.: **20404**

VIDEO
GF7.5-GF11
Click here Video



Cross section



RTG Ø 12 mm

RTG Ø 6 mm

incl. connection thread
(for flexible leading head or small-sized cable pulling grip)
incl. blind cap
(for thread proctection)

Click here Productinformation

Application images



Can be adapted to roller, shackle and starting head Ø 20 mm, Ø 30 mm



DATA

ITEM NO.	**20404**
WEIGHT	0,207 kg
DIMENSION	L 65 mm x B 38 mm x DM 30 mm
THREAD	RTG Ø 12 mm
MATERIAL	Stainless steel
EAN-CODE	9120045474398

ADVANTAGES

- RUNPOTEC RTG Ø 12 mm
- For guide probe or smaller cable pulling grips
- Incl. connecting thread
- Stainless steel
- Leanest head

DESCRIPTION

Starting head Ø 30 mm made of stainless steel for fiberglass rod GF7.5 - GF15 - RTG Ø 12 mm thread. The starting head has an additional transition thread to RTG Ø 6 mm to adapt various guide rods (RUNPOSTICKS), guide probes, cable pulling grip (sock) etc.

Scope of supply: 1 x Starting head Ø 30 mm with thread RTG Ø 12 mm, 1x connection thread RTG Ø 6 mm

INFORMATION

Compatible with:
Fiberglass rods:
GF7.5, GF9, GF11, GF15



Click here Productinformation